

A New Energy Experience

AMBEROCK

Portable power supply
AR2000



Charging versatile, Powerful to the point of being friendless

× 4
USB-C

× 2
USB-A

× 1
Wireless
charging

× 4
AC port

6 types of interfaces can simultaneously power
up to 13 devices, catering to various scenario
needs.




Core is tough, truly stable.



UN38.3



AR 2000 is compliant with the EU's New Battery Regulation (EU) 2023/1542 and meets more than 40 international standards. The battery cells have undergone multiple rounds of rigorous tests, including needle penetration, hermal propagation, crushing, and drop, fully ensuring your power safety.



Fear no awkward silence, call now.

-20°C

Minimum operating
temperature

40°C

Maximum operating
temperature

Built-in heating film, supports charging and
discharging heating, can achieve your electricity
freedom even in low-temperature conditions.



Energy at your fingertips.

The AR2000 remote control and management support functions are implemented through the Voltdeer App:

- Monitor device data such as battery level, remaining usage time, and input/output power.
- Receive real-time alerts for warning and protection information.
- Perform OTA firmware upgrades for the device.
- Customize AC switch, charge-discharge timing functions, heating film timing functions, etc., to create your exclusive power usage plan.



Long-lasting battery life, a reliable partner.

Built-in LiFePO₄ battery, cycle life up to 3000+.



3000+

Travel, even better.

3hrs

 Solar panel charging



Recommended to be paired with solar panels of 800W or higher.

2hrs

 AC charging



3hrs

 Car charging



2400Wh large capacity.



Mobile phone
3300 mAh
Charges about
180 times



Game console
15 Wh
Charges about
144 times



Laptop
60 Wh
Charges about
36 times



Drone
20 Wh
Charges about
108 times



Camera
8 Wh
Charges about
270 times



Flashlight
5 W
Approximately
432 hours



Car refrigerator
60 W
Approximately
36 hours



LCD TV
100 W
Approximately
21.6 hours



Coffee machine
800 W
Approximately
2.7 hours



Handheld drill
1000 W
Approximately
2.16 hours



Expand freely, double the energy.

With the extended battery pack EZ2000, the total capacity can be increased to a maximum of 4.8 kWh.



AR2000
2400 Wh




EZ2000
2400 Wh

Optional accessories



Storage bag



Solar panel



Pulley

Specification table

Battery

Capacity	2400 Wh
Type	Lithium Iron Phosphate

Basic Information

Dimensions (L × W × H)	390 × 230 × 375 mm
Weight	26.5kg
Protection Level	IP20
Cooling Method	Forced air cooling
Communication	RS485, CAN, WiFi, BLE
Cycle life (25 °C, 80%EOL) >	>3000
Extension Pack	Supports
App	Android, iOS
Certification	RCM, CE, UN38.3,UL

Output

AC Output (x 4)	230 V~10 A, 2200 VA(rated), 4000 VA (peak)
Cigarette Lighter Output (x 1)	12 V = 10 A
USB-A output (x 2)	12 V = 2 A/9 V = 2.5 A/5 V = 3 A, 24 W Max
USB-C output (x 4)	20 V = 5 A/20 V = 3 A/15 V = 3 A/12 V = 3 A/9 V = 3 A/5 V = 3 A, 105 W Max
Expansion interface output (x 1)	48 V = 40 A, 2000 W Max
Wireless charging output (x 1)	15 W Max

Input

Solar input	800 W, 12 V~60 V = 25 A Max
Car charger input	11 ~ 14 V (12 V platform) = 8 A 2128 V (24 V platform) = 8 A
Expansion interface input	54 V = 30 A
AC input	220 V~240 V, 1800 VA Max

Environmental parameters

Discharge Temperature - -20~ 40 °C

Charging Temperature -20~ 40 °C

*When the temperature is lower than 5°C, the heating film will automatically turn on to ensure normal charging and discharging of the battery.

Storage and transportation temperature
Short term: -20 ~ 40 °C
Long term: 20 ~ 30 °C

Relative Humidity 0 ~ 85%(No condensation)

Altitude ≤ 2000 m

VOLTDEER

Shanghai Voltdeer Technology Co.,Ltd.
Building 14, No.739 Kangwei Road,Pudong New Area, Shanghai

wdkj@voltdeer.com

There may be differences between the pictures in this manual and the actual product. Please refer to the actual product.
Information contained in this manual is subject to change without prior notice.

Made from recycled paper